

Stamped Steel 3-Bolt Flange Cartridge Units

SBPF
Cylindrical bore
(with set screws)
 d 12 ~ 35 mm



SAPF
Cylindrical bore
(with eccentric locking collar)



SBPF



SAPF



Shaft Dia mm inch		Dimensions inch mm								Bolt Size inch mm	Unit No.	Bearing No.			
d		H	A	A_1	J	N	H_2	S	SBPF B				SAPF B_1		
12															
15	1/2	3 3/16	9/16	5/32	2 1/2	9/32	1 15/16	0.236	0.866	1.122	1/4	SBPF201	SB201		
	5/8	81	14	4	63.5	7.1	49	6	22	28.5	M6	SBPF201-8	SB201-8		
17															
												SBPF202	SB202		
20	3/4	3 17/32	5/8	5/32	2 13/16	23/64	2 5/32	0.276	0.984	1.161	5/16	SBPF202-10	SB202-10		
		90	16	4	71.5	9	55	7	25	29.5	M8	SBPF203	SB203		
25	7/8														
	15/16	3 3/4	23/32	5/32	2 63/64	23/64	2 3/8	0.295	1.063	1.201	5/16	SBPF204-12	SB204-12		
30	1	95	18	4	76	9	60	7.5	27	30.5	M8	SBPF205	SB205		
												SBPF205-16	SB205-16		
35	1 1/8														
	1 3/16	4 7/16	3/4	13/64	3 9/16	7/16	2 25/32	0.315	1.181	1.335	3/8	SBPF206-18	SB206-18		
35	1 1/4	113	19	5.2	90.5	11	71	8	30	33.9	M10	SBPF206	SB206		
	1 5/16											SBPF206-19	SB206-19		
35	1 3/8	4 13/16	7/8	13/64	3 15/16	7/16	3 3/16	0.335	1.260	1.437	3/8	SBPF206-20	SB206-20		
	1 7/16	122	22	5.2	100	11	81	8.5	32	36.5	M10	SBPF207-20	SB207-20		
												SBPF207-22	SB207-22		
												SBPF207	SB207		
												SBPF207-23	SB207-23		

Note 1) H_2 is the minimum size of the mounting hole.