











- Cables for Old Model Force Gauge, Torque Gauge and Amplifier

| Type of Cable | Model | Image | Compatible Gauges | External Device | Description | Length |
|-------------------------|--------|---|--------------------------|--|--|--|
| Analog Cable | CB-101 |  | DS2 | Analog device (Pen Recorder, Oscilloscope, Multi Meter etc.) | Connects to an analog device to enable voltage output. | Approx.3m |
| | CB-104 |  | ZP Z2 HTG2 DTX2 | Analog device (Pen Recorder, Oscilloscope, Multi Meter etc.) | Connects to an analog device to enable voltage output. | Approx.3m |
| RS232C Cable | CB-204 |  | ZP Z2 HTG2 DTX2 | PC, PLC | Enables data recording and operation from external device. The connector shape on the external device connection side is D-Sub 9-pin (female). | Approx.3m |
| Digimatic Cable | CB-301 |  | DS2 | Mitutoyo Digimatic Printer | Enables to print out the measured values. | Approx.3m |
| | CB-304 |  | Z2 HTG2 DTX2 | Mitutoyo Digimatic Printer | Enables to print out the measured values. | Approx.3m |
| Test Stand Option Cable | CB-501 |  | ZP Z2 | Motorized Test Stand MX series MH series | Activates test stand's functions such as overload prevention and force control. | Approx.1.2m |
| | CB-504 |  | ZP Z2 | Motorized Test Stand MX series MH series | Connect ZP/Z2 with Mx test stand and PC, activates test stand's functions such as overload prevention and force control. | Gauge side: Approx.1.2m PC side: Approx. 2m |
| | CB-705 |  | FA Plus | Motorized Test Stand EMX series with firmware earlier than ver.2.0 | Activates test stand's functions such as overload prevention and displacement I/O. | Approx.1.5m |
| | CB-704 |  | ZP Z2 | Motorized Test Stand MX2series EMX series with firmware earlier than ver.2.0 | Activates test stand's functions such as overload prevention and force control. | Approx.1.5m |
| | CB-707 |  | FA Plus | Motorized Test Stand MX2-FA series EMX-FA series with firmware ver.2.0 or later | Activates test stand's functions such as overload prevention and force control. | Approx.1m |

* Different cables are not able to connect to the same connector. We offer custom made options to allow using two different cables at the same time.