

タップドブラインドノブ BTK Tapped Blind Knobs BTK, BTK-sus

BTK BTK-sus

RoHS指令適合品







BTK

材 ノブ : 黒色フェノール樹脂
Phenolic plastic Black
ネジ : 黄銅C3604B brass

BTK-sus

材 ノブ : 黒色フェノール樹脂
Phenolic plastic Black
ネジ : ステンレスSUS303 Stainless



Unit : mm

品番	D	M	ℓ	d	H	h	h1	(g)	
BTK-30-A	32	M 5 × P0.8	10	19	23	11	0.3	16	
BTK-30-B		M 6 × P1.0	12					19	
BTK-40-A	40	M 8 × P1.25	13	21	27	12		27	
BTK-40-B			13					21	31
BTK-50-A	50	M10 × P1.5	20	25	33	14		50	
BTK-50-B			17					25	52
BTK-60-A	60	M12 × P1.75	20	27	37	17		76	
BTK-60-B								20	27
BTK-70	70			30	44	20			119
BTK-85	85	M16 × P2.0	22	35	55	30			176

Unit : mm

品番	D	M	ℓ	d	H	h	h1	(g)
BTK-30-sus	32	M 6 × P1.0	12	19	23	11	0.3	18
BTK-40-sus	40	M 8 × P1.25	13	21	27	12		30
BTK-50-sus	50	M10 × P1.5	17	25	33	14		50
BTK-60-sus	60	M12 × P1.75	20	27	37	17		78

注意事項 使用温度 max110°C min-20°C