

スパイラルダクト直管寸法表

■ スパイラルダクト直管寸法表

単位(mm)

呼径	管厚	各部寸法			参考重量	呼径	管厚	各部寸法			参考重量
D	t	W	P	D ₁	kg/m	D	t	W	P	D ₁	kg/m
75	0.5	6	60	79.0	1.2	400	0.6	7	135	404.0	7.1
100	0.5	6	87	104.0	1.6		0.8	8	127	406.4	9.8
	0.6	7	//	104.8	1.9		1.0	10	126	408.0	12.2
125	0.8	8	//	106.4	2.5	450	0.6	7	135	454.8	8.0
	0.5	6	86	129.0	2.0		0.8	8	127	456.4	11.1
	0.6	7	//	129.8	2.4		1.0	10	125	458.0	13.7
150	0.8	8	//	131.4	3.1	500	0.6	7	134	504.8	8.8
	0.5	6	140	154.0	2.2		0.8	8	126	506.4	12.3
	0.6	7	140	154.8	2.7		1.0	10	125	508.0	15.2
175	0.8	8	131	156.4	3.7	550	0.6	7	134	554.8	9.7
	1.0	10	130	158.0	4.6		0.8	8	126	556.4	13.5
	0.5	6	138	179.0	2.6		1.0	10	125	558.0	16.7
200	0.6	7	138	179.8	3.1	600	0.6	7	134	604.8	10.6
	0.8	8	129	181.4	4.3		0.8	8	126	606.4	14.7
	1.0	10	128	183.0	5.3		1.0	10	125	608.0	18.2
225	0.5	6	137	204.0	2.9	650	0.8	8	126	656.4	15.9
	0.6	7	137	204.8	3.5		1.0	10	125	658.0	19.7
	0.8	8	129	206.4	4.9		700	0.8	8	126	706.4
1.0	10	128	208.0	6.1	1.0	10		125	708.0	21.3	
0.5	6	136	229.0	3.3	750	0.8		8	126	756.4	18.4
0.6	7	136	229.8	4.0		1.0	10	125	758.0	22.8	
0.8	8	128	231.4	5.5		800	0.8	8	126	806.4	19.6
1.0	10	127	233.0	6.8	1.0		10	125	808.0	24.3	
0.5	6	136	254.0	3.7	850		1.0	10	125	858.0	25.8
0.6	7	136	254.8	4.4		900	1.0	10	125	908.0	27.3
0.8	8	128	256.4	6.1			950	1.0	10	125	958.0
1.0	10	127	258.0	7.6	1000			1.0	10	125	1008.0
0.5	6	136	279.0	4.0		300		0.6	7	135	329.8
0.6	7	136	279.8	4.9			0.8	8	127	331.4	8.0
0.8	8	127	281.4	6.7	1.0		10	126	333.0	9.9	
1.0	10	126	283.0	8.4	325	0.6	7	135	354.8	6.2	
0.5	6	135	304.0	4.4		0.8	8	127	356.4	8.6	
0.6	7	135	304.8	5.3		1.0	10	126	358.0	10.7	
0.8	8	127	306.4	7.4	350	0.6	7	135	379.8	6.6	
1.0	10	126	308.0	9.1		0.8	8	127	381.4	9.2	
0.6	7	135	329.8	5.7		1.0	10	126	383.0	11.4	
0.8	8	127	331.4	8.0	375	0.6	7	135	379.8	6.6	
1.0	10	126	333.0	9.9		0.8	8	127	381.4	9.2	
0.6	7	135	354.8	6.2		1.0	10	126	383.0	11.4	

(注) 出荷工場により一部の製品は、寸法および仕様が異なる場合があります。詳しくはお問い合わせ下さい。〔定尺は4mです〕