



〈SS 規格〉

呼び番号	Oリングの寸法			
	太さ	d2	内径 d1	
SS-005	1	± 0.05	0.5	± 0.10
SS-008			0.8	
SS-010			1	
SS-012			1.2	
SS-015			1.5	
SS-018			1.8	
SS-020			2	
SS-022			2.2	
SS-025			2.5	
SS-028			2.8	
SS-030			3	
SS-032			3.2	
SS-035			3.5	
SS-038			3.8	
SS-040			4	
SS-042			4.2	
SS-045			4.5	
SS-048			4.8	
SS-050			5	
SS-055			5.5	
SS-060			6	
SS-065			6.5	
SS-070			7	
SS-075			7.5	
SS-080			8	
SS-085			8.5	
SS-090			9	
SS-095			9.5	
SS-100			10	
SS-105			10.5	
SS-110			11	
SS-115			11.5	
SS-120			12	
SS-125			12.5	
SS-130			13	
SS-135			13.5	
SS-140			14	
SS-145			14.5	
SS-150			15	
SS-155			15.5	
SS-160	16			
SS-165	16.5			
SS-170	17			
SS-175	17.5			
SS-180	18			
SS-185	18.5			
SS-190	19			
SS-195	19.5			
SS-200	20			

〈GM 規格〉

呼び番号	Oリングの寸法			
	太さ	d2	内径 d1	
GM-005	5	± 0.12	5	± 0.15
GM-010			10	
GM-015			15	
GM-020			20	
GM-025			25	
GM-030			30	
GM-035			35	
GM-040			40	
GM-045			45	
GM-050			50	
GM-055			55	
GM-060			60	
GM-065			65	
GM-070			70	
GM-075			75	
GM-080			80	
GM-085			85	
GM-090			90	
GM-095			95	
GM-100			100	
GM-105			105	
GM-110			110	
GM-115			115	
GM-120			120	
GM-125			125	
GM-130			130	
GM-135			135	
GM-140			140	
GM-145			145	
GM-150			150	
GM-155	155			
GM-160	160			
GM-165	165			
GM-170	170			
GM-175	175			
GM-180	180			
GM-185	185			
GM-190	190			
GM-195	195			
GM-200	200			
GM-205	205			
GM-210	210			
GM-215	215			
GM-220	220			
GM-225	225			
GM-230	230			
GM-235	235			
GM-240	240			
GM-245	245			
GM-250	250			
GM-255	255			
GM-260	260			
GM-265	265			
GM-270	270			
GM-275	275			
GM-280	280			
GM-285	285			
GM-290	290			
GM-295	295			
GM-300	300			

SS, GM