



## CoroMill® 390 square shoulder milling cutter

Weldon




KAPR

90°



## Metric version

| DC   | CZC <sub>MS</sub> | APMX | RMPX  | AZ    | CNCS | Ordering code | Dimensions      |      |      |       |      |     |      | CIC   | MIID |           |
|------|-------------------|------|-------|-------|------|---------------|-----------------|------|------|-------|------|-----|------|-------|------|-----------|
|      |                   |      |       |       |      |               | DCON            | DCX  | LF   | LU    | Nm   | kg  | RPM  |       |      |           |
| 12.0 | 11                | 16   | 10.0  | 6.0°  | 1.0  | 1             | R390-012B16-11L | 16.0 | 12.0 | 68.0  | 17.2 | 1.2 | 0.23 | 68600 | 1    | R390-11.. |
| 16.0 | 11                | 16   | 10.0  | 10.5° | 1.0  | 2             | R390-016B16-11L | 16.0 | 16.0 | 73.0  | 25.0 | 1.2 | 0.22 | 41500 | 2    | R390-11.. |
| 20.0 | 11                | 20   | 10.0  | 5.5°  | 1.0  | 1             | R390-020B20-11L | 20.0 | 20.0 | 81.0  | 25.0 | 1.2 | 0.29 | 34600 | 2    | R390-11.. |
|      |                   |      |       |       |      |               | R390-020B20-11M | 20.0 | 20.0 | 81.0  | 25.0 | 1.2 | 0.29 | 34600 | 3    | R390-11.. |
| 25.0 | 11                | 25   | 10.0  | 5.0°  | 1.0  | 1             | R390-025B25-11L | 25.0 | 25.0 | 88.0  | 32.0 | 1.2 | 0.41 | 36500 | 2    | R390-11.. |
|      |                   |      |       |       |      |               | R390-025B25-11M | 25.0 | 25.0 | 88.0  | 32.0 | 1.2 | 0.38 | 36500 | 3    | R390-11.. |
|      |                   |      |       |       |      |               | R390-025B25-11H | 25.0 | 25.0 | 88.0  | 32.0 | 1.2 | 0.38 | 36500 | 4    | R390-11.. |
| 17   | 25                | 15.7 | 15.5° | 1.5   | 1    | 2             | R390-025B25-17L | 25.0 | 25.0 | 88.0  | 32.0 | 3.0 | 0.41 | 30800 | 2    | R390-17.. |
|      |                   |      |       |       |      |               | R390-032B32-11L | 32.0 | 32.0 | 100.0 | 40.0 | 1.2 | 0.65 | 31000 | 2    | R390-11.. |
|      |                   |      |       |       |      |               | R390-032B32-11M | 32.0 | 32.0 | 100.0 | 40.0 | 1.2 | 0.68 | 31000 | 3    | R390-11.. |
| 32.0 | 11                | 32   | 10.0  | 3.6°  | 1.0  | 1             | R390-032B32-11H | 32.0 | 32.0 | 100.0 | 40.0 | 1.2 | 0.65 | 31000 | 5    | R390-11.. |
|      |                   |      |       |       |      |               | R390-032B32-17L | 32.0 | 32.0 | 100.0 | 40.0 | 3.0 | 0.80 | 25600 | 2    | R390-17.. |
|      |                   |      |       |       |      |               | R390-032B32-17M | 32.0 | 32.0 | 100.0 | 40.0 | 3.0 | 0.61 | 25600 | 3    | R390-17.. |
|      |                   |      |       |       |      |               | R390-040B32-11L | 32.0 | 40.0 | 110.0 |      | 1.2 | 0.85 | 27000 | 2    | R390-11.. |
|      |                   |      |       |       |      |               | R390-040B32-11M | 32.0 | 40.0 | 110.0 |      | 1.2 | 0.81 | 27000 | 4    | R390-11.. |
| 11   | 32                | 10.0 | 2.0°  | 1.0   | 1    | 1             | R390-040B32-11H | 32.0 | 40.0 | 110.0 |      | 1.2 | 0.84 | 27000 | 6    | R390-11.. |
|      |                   |      |       |       |      |               | R390-040B32-17L | 32.0 | 40.0 | 110.0 |      | 3.0 | 0.81 | 21900 | 2    | R390-17.. |
|      |                   |      |       |       |      |               | R390-040B32-17M | 32.0 | 40.0 | 110.0 |      | 3.0 | 0.80 | 21900 | 3    | R390-17.. |
|      |                   |      |       |       |      |               | R390-040B32-17H | 32.0 | 40.0 | 110.0 |      | 3.0 | 0.80 | 21900 | 4    | R390-17.. |



J112



O5




Q5



Q1



Q35



Q16