

# 油圧用継手

—Hネジ・PTネジ—

選定手順①～③より型式・数値を選択の上、ご注文ください。



Order  
注文例



型式 (①Type・②No.・③管ねじ)

TH02H03T

型式 (Type・No.)


THU02H

## ■おねじ接続



材質 SUS304

## ■おねじストレート継手





材質 SUS304

型式			T <sub>1</sub>	T <sub>2</sub>	L	E	E <sub>1</sub>	B
①Type	②No.	③管ねじ						
TH	02H	03T	1/4H	1/8PT	29	4.8	4.8	12
		06T		1/4PT	33		7	14
		10T		3/8PT	34		9.6	17
		15T		1/2PT	39		12	22
	03H	03T	3/8H	1/8PT	30.5	7	4.8	16
		06T		1/4PT	34		7	17
		10T		3/8PT	35		9.6	17
		15T		1/2PT	40		12	22
	04H	06T	1/2H	1/4PT	37	10	7	19
		10T		3/8PT	38		9.6	19
		15T		1/2PT	43		12	22
		20T		3/4PT	46		16	27
	05H	15T	5/8H	1/2PT	44	12	12	23
		10T		3/8PT	43		9.6	27
	06H	15T	3/4H	1/2PT	47	16	12	27
		20T		3/4PT	49		16	27
25T		1PT		52	22		35	
20T		3/4PT		52	16		35	
08H	25T	1H	1PT	54	21	22	35	

型式			T <sub>1</sub>	T <sub>2</sub>	L <sub>1</sub>	L <sub>2</sub>	E	E <sub>1</sub>
①Type	②No.	③管ねじ						
THE	02H	03T	1/4H	1/8PT	25	25	4.8	4.8
		06T		1/4PT	23.5	23.5		7
		10T		3/8PT	26	26		9.6
		06T		1/4PT				7
	03H	10T	3/8H	3/8PT	30.5	30.5	7	9.6
		15T		1/2PT				12
		06T		1/4PT				31
	04H	10T	1/2H	3/8PT	33	33	10	9.6
		15T		1/2PT	31	31		12
		20T		3/4PT	36	36		16
		05H		15T	5/8H	1/2PT		30.5
	15T	3/4PT	35.5	35.5		16	16	
	06H	20T	3/4H	3/4PT	42	42	16	16
		25T		1PT	41	41		21
	08H	25T	1H	1PT	41	41	21	22

## ■ユニオン継手




材質 SUS304

型式		T	L	E	B
Type	No.				
THU	02H	1/4H	33	4.8	14
	03H	3/8H	35	7	16
	04H	1/2H	42	10	19
	06H	3/4H	49	16	27
	08H	1H	54	21	35

## ■オス・オスエルボ

ELM□T



材質 SUS304

型式		P (PT)	A	C	L±0.25	E±0.1	R
Type	No.						
ELM	03T	1/8	11±0.3	9	19.5	4.8	R0.5
	06T	1/4	14.5±0.3	12	24.3	7	
	10T	3/8	18.6±0.3	13	26.7	9.6	
	15T	1/2	22.7±0.4	17	31.7	12	R1
	20T	3/4	27.5±0.5	18	36.3	16	
	25T	1	34±0.5	20	42.5	22	

## ■Hネジ(参考表)

Hネジ	UNF規格ねじ
1/4H	7/16—20
3/8H	9/16—18
1/2H	3/4—16
5/8H	7/8—14
3/4H	1 1/16—12
1H	1 5/16—12