















Ferrule, uninsulated,
tin plated,
electrolytic copper,
gastight crimped



Item No.	Pack. Unit	Ferrules		
Ferrule, uninsulated, according to DIN 46228, part 1/08.92		Technical Data		
216-151	1000	 sleeve for 0.34 mm ² /AWG 24, 7 mm strip length, L: 7 mm, D: 1.7 mm, D2: 0.85 mm	 sleeve for 1 mm ² /AWG 18, 8 mm strip length, L: 8 mm, D: 2.5 mm, D2: 1.4 mm	
216-131	1000			
216-152	1000			
216-132	1000			
216-121	1000			
216-101	1000			
216-122	1000			
216-102	1000	 sleeve for 0.5 mm ² /AWG 22, 6 mm strip length, L: 6 mm, D: 2.1 mm, D2: 1 mm	 sleeve for 1.5 mm ² /AWG 16, 6 mm strip length, L: 6 mm, D: 2.8 mm, D2: 1.7 mm	
216-123	1000			
216-103	1000			
216-124	1000			
216-104	1000			
216-106	1000			
216-107	1000			
216-108	250			
216-109	250			
216-110	250			
Ferrules		Technical Data		
Technical Data				
 sleeve for 0.25 mm ² /AWG 24, 5 mm strip length, L: 5 mm, D: 1.7 mm, D2: 0.75 mm		 sleeve for 0.75 mm ² /AWG 20, 6 mm strip length, L: 6 mm, D: 2.3 mm, D2: 1.2 mm	 sleeve for 2.5 mm ² /AWG 14, 10 mm strip length, L: 10 mm, D: 3.4 mm, D2: 2.2 mm	
216-151		216-122	216-106	
 sleeve for 0.25 mm ² /AWG 24, 7 mm strip length, L: 7 mm, D: 1.7 mm, D2: 0.75 mm		 sleeve for 0.75 mm ² /AWG 20, 8 mm strip length, L: 8 mm, D: 2.3 mm, D2: 1.2 mm	 sleeve for 4 mm ² /AWG 12, 10 mm strip length, L: 10 mm, D: 4 mm, D2: 2.8 mm	
216-131		216-102	216-107	
 sleeve for 0.34 mm ² /AWG 24, 5 mm strip length, L: 5 mm, D: 1.7 mm, D2: 0.85 mm		 sleeve for 1 mm ² /AWG 18, 6 mm strip length, L: 6 mm, D: 2.5 mm, D2: 1.4 mm	 sleeve for 6 mm ² /AWG 10, 12 mm strip length, L: 12 mm, D: 4.7 mm, D2: 3.5 mm	
216-152		216-123	216-108	