

Trim Seals

Trim Seals are available in 1m increment. Please note that ordering 5 pieces of L=100 means 5 rolls of 100 meter type.

RoHS10

TRSAT
TRSBT
TRCCT
TRSDT

TRSASB (Black)
TRSASG (Gray)

TRSBBSB (Black)
TRSBBSG (Gray)

TRSCSB (Black)
TRSCSG (Gray)

Bending Directions

Rubber Position Y

Rubber Position X

Type	Material			Color
	Main Body	Rubber Part	Internal Metal Strip	
TRS□T	Thermoplastic Elastomer (TPE)	EPDM	Aluminum	Black
TRS□SB	Silicon Rubber	Silicon Rubber	SPCC	Black
TRS□SG	Silicon Rubber	Silicon Rubber	SPCC	Gray

Part Number Type	T	Rubber Position	L	A	B	C	W	D	t	Minimum Bending Radius mm			Applicable Plate Thickness (T Range)														
										Bending Directions ①	Bending Directions ②	Bending Directions ③															
TRSAT	1.6	X (Solid Line)	L1-L100 (1m Increment)	6.0	14.5	15.4	1.6	9.5	1.3	30	30	30	1.2-2.4														
	3.2			7.6	14.0	17.0	3.2						2.4-4.0														
	4.8			9.2	13.3	18.6	4.8						4.0-5.0														
	6.4			10.8	12.7	20.2	6.4						5.5-6.4														
TRSBT	1.6			Y (Dotted Line)	L1-L100 (1m Increment)	6.0	14.5	17.0	1.6	11.1	1.5	30	30	50	1.2-2.4												
	3.2					7.6	14.0	18.6	3.2						2.4-4.0												
	4.8					9.2	13.3	20.2	4.8						4.0-5.0												
	6.4					10.8	12.7	21.8	6.4						5.5-6.4												
TRCCT	1.6					X(Solid Line)	L1-L75 (1m Increment)	6.0	14.5	21.7	1.6	15.9	2.0	60	60	70	1.2-2.4										
	3.2							7.6	14.0	23.3	3.2						2.4-4.0										
	4.8							9.2	13.3	24.9	4.8						4.0-5.0										
	6.4							10.8	12.7	26.5	6.4						5.5-6.4										
TRSDT	1.6	-	L1-L75 (1m Increment)					5.4	9.1	12.3	1.6	7.0	1.3	30	30	-	1.2-1.6										
TRSASB	3.2							9.6	13.2	24.0	4.6						10.0	1.2	95	170	50	1.0-3.2					
TRSASG								9.6	13.2	20.0	4.6											10.4	1.2	50	50	-	1.0-3.2
TRSBBSB								3.2	9.6	13.2	18.5											4.6	6.5	1.2	50	90	35
TRSBBSG	9.6			13.2	18.5				4.6	6.5	1.2	50	90	35	1.0-3.2												
TRSCSB	3.2			-	L1-L75 (1m Increment)			9.6	13.2	18.5	4.6	6.5	1.2	50	90	35	1.0-3.2										
TRSCSG								9.6	13.2	18.5	4.6						6.5	1.2	50	90	35	1.0-3.2					

⚠ L Dimension is specified in 1m increment.

⚠ Minimum bending radius value is experimental ones and not guaranteed. Use them as reference. (Applicable to both rubber positions X and Y.)




Ordering Example


Part Number	-	Rubber Position	-	L
TRCCT1.6	-	X	-	L15
TRSCSB3.2	-	-	-	L58

Part Number Type	T	Rubber Position	L	Unit Price/m												
				1-4m	5-9m	10-14m	15-29m	30-74m	75-99m	100m						
TRSAT	1.6	X (Solid Line)	L1-L100 (1m Increment)													
	3.2															
	4.8															
	6.4															
TRSBT	1.6			Y (Dotted Line)	L1-L100 (1m Increment)											
	3.2															
	4.8															
	6.4															
TRCCT	1.6					X(Solid Line)	L1-L75 (1m Increment)									
	3.2															
	4.8															
	6.4															
TRSDT	1.6	-	L1-L75 (1m Increment)													
TRSASB	3.2															
TRSASG																
TRSBBSB								3.2								
TRSBBSG																
TRSCSB	3.2			-	L1-L75 (1m Increment)											
TRSCSG																

ex Example



For Rubber Position X



For Rubber Position Y

⚠ Best when rubber O.D. dimension is compressed to 40 ~ 60% of the standard dimension.