




Part Number	Mass	Applic	able S	Screw, T N	Allowable Load	Unit Price	Volume Discount Rate	
Part Number	(g)	Screw	Quantity	T Nut	Quantity	(N)	1~99 pc(s).	100~200
HBLFSNK8	50	CBM8-20	2	HNTT8-8	2	2058		
HBLFSNE8	50	ODIVIO-20	2	11IV110-0	2	2000		





Features: Pressing nuts against the long tabs makes cumbersome hole positioning unnecessary.







Slotted holes are for various nut hole positions.
Bracket tabs may be damaged

when nuts are fallen on them.

• Use of washers are recommended.
(Refer to alterations below: SEC)

Material: ADC12





Part	Mass	Applic	able S	Screw, T Nu	Allowable Load	Unit Price	Volume Discount Rate	
Number	(g)	Screw	Quantity	T Nut	Quantity	(N)	1~99 pc(s).	100~200
HBLFSR8	55	CBM8-20	2	HNTT8-8	2	2058		



When nuts are wedged through until the tab, hole positions of bracket and nuts are aligned and fine adjustment becomes unnecessary.


Short Nuts, HNTM and HNTAM are


not applicable.




Features: Tabbed Reversal Brackets with Cover. Designed to prevent dust build-up.










Ī					Screw, T								
	Number	(g)	Screw	Quantity	T Nut	Quantity	Part ¹	Quantity	Part ²	Quantity	(N)	1~99 pc(s).	100~200
Ī	HBLFSNT8	56	CBM8-20	2	HNTT8-8	2	Bracket Body	1	Bracket Cover	1	2058		









Ordering Part Number Example HBLFSNK8

Alterations Part Number

(C, SET, SST, SEU, SSU, SEP, SSP, SEC)

Alterations	Code	Spec.	Applicable Bracket
Mounting Hole Alteration for Cover	С	Adds taps on a bracket for cover mounting. (M5 on Both Sides) (Mounting Screw HCBM on P.754)	HBLFSNF8 HBLFSNB HBLFSNBB HBLFSNBB HBLFSSNBB HBLFSBB HBLFSBB HBLFSLB HBLFSNKB HBLFSNKB HBLFSNKB HBLFSNKB

Alterations	Code	Spec.			Applicable Bracket				
	CET		le screws and n on extrusions c	uts for fixing the ome in a set.	HBLFSNF8				
	SET SST		the bracket pric		HBLFSN8				
	(Stainless Steel)		/hen HBLFS	8 is	HBLFSNB8				
	Pre-Assembly Insertion Spring Nuts	specif	ied:		HBLFSNM8				
	SSU	Code	Screw	Nut	CHBLFSN8				
	/ Pre-Assembly Insertion \	SET	CBM8-20	HNTT8-8	CHBEFSNO				
Applicable	Spring Nuts Stainless Steel	SST	SCB8-20	HNTTSN8-8	HBLFS8				
Screws and Nuts Set	SEP / / Post-Assembly Insertion \	SEU	CBM8-20	HNTU8-8	HBLFSB8				
	Spring Nuts	SSU	SCB8-20	SHNTU8-8	HBLFSL8				
	SSP / Post-Assembly Insertion \	SEP	CBM8-20	HNTP8-8					
	Spring Nuts Stainless Steel	SSP	SCB8-20	SHNTP8-8	HBLFSNK8				
	SEC Screws with Captured Washer and	SEC	HCBST8-24	HNTT8-8	HBLFSNE8				
			en specifyin		HBLFSR8				
	\ Nuts /	than HBLFS8, check for the applicable screws and nuts.			HBLFSNT8				
Screws for	Screws for Black Anodized Brackets and Cathodic Electrodenosition Painted (black) Brackets are								

- HCBMTB (Trivalent Chromate Black) on P.751.
- Included Screw is not RoHS compliant when -SET, -SEU or -SEP other than Black Anodized or Cathodic Electrodeposition Painted (black) Brackets is specified.