

Free Angle Brackets

For 8-45 Series (Slot Width 10mm) Aluminum Extrusions







Part Number Applica		Applicable	Mass			Unit Price	Volume Discount Rate
	No.		(g)	Accessory	Quantity	1 ~ 14 pc(s).	
HBLTBA		45 Square (HFS8-45)	113	M10x16	1		
HBLTBBN	AE		116				
HBLTBC	45 43		299	CLDMC8-50-M	1		
HBLTBD			301				







Part Number - (SET · SET1 · SET2 · SET3 · SET4 · SET5)

Alterations HBLTBA45 - SET2

Altorations	Codo	How to Use	Part Number		Accessory				
Aiterations	Code	now to use	Type	No.	Screw	Quantity	Nuts, Pre-Assembly Insertion Double Joints	Quantity	
	SET		HBLTBBN		CBM6-35	2	HDJFSN8-45	1	
	SET1	Use the hole 1	HBLTBA	45	CBM8-20	2	HNTT8-8	2	
	SET2	Use the hole 2	HDLIDA		CBM8-20	1	HNTT8-8	1	
Applicable Screws and	SET3	Use the hole 1	нвітвс		CBM6-35	2	HDJFSN8-45	1	
Nuts Set					CBM8-20	2	HNTT8-8	2	
	SET4	Use the hole 2	нвітвс		CBM6-35	2	HDJFSN8-45	1	
	SE14				CBM8-20	1	HNTT8-8	1	
	SET5		HBLTBD		CBM6-35	4	HDJFSN8-45	2	


When connecting with Pre-Assembly Insertion Double Joints, S type hole machining (P.765) is required on extrusions. ♠Included Screw is not RoHS compliant when -SET is specified

Example

(1) Connection of Two End Sections


HBLTBA45


Two pieces of HBLTBBN are used to connect two end sections using Pre-Assembly Insertion Double Joints (P.709). (With Clamp Lever Type: HBLTBD45)



(2) Connection of Two Side Faces

To the extrusion side face, connect with HBLTBA, a screw and a nut. To the end face, use 1 HBLTBBN for 1 HBLTBA using Pre-Assembly Insertion Double Joint. (With Clamp Lever Type: HBLTBC45)





Two pieces of HBLTBA are used to connect them with extrusion side using screws and nuts.














(See P709)

Features: Sheet Metal Brackets to fix at arbitrary positions.









Part Number		Applicable	Applicable Screw and Nut				Unit Price	Volume Discount Rate	
	Туре	No.		Hex Socket Head Cap Screws with Captured Washer	Quantity	Nut	Quantity	1~99 pc(s).	100~150
	HBLPBL HBI PBR	8-45	45 Square (HFS8-45)	CBST8-15	4	HNTT8-8	4		

Туре	No.	Extrusion	Hex Socket Head Cap Screws with Captured Washer	Quantity	Nut	Quantity	1~99 pc(s).	100~15
HBLPBL HBLPBR	8-45	45 Square (HFS8-45)	CBST8-15	4	HNTT8-8	4		
							n.	





Alterations	Code	Spec.	Applicable Bracket		
Applicable Screws and Nuts Set	SET	Supplies a set of applicable screws and nuts for fixing the bracket to a extrusion.	HBLPBL8-45 HBLPBR8-45		
Set with applicable screws, nuts and clamp levers	SET1	Applicable Screw: 3 pcs. Clamp Lever (LNP): 1 pc. Flat Washer (PWF) 1 pc. Applicable Nut: 4 pcs. Set with the above items.	HBLPBL8-45 HBLPBR8-45		

Example