


# Terminal Blocks - Hydraulic / Pneumatic

## L-Shaped Hole



For details of recommended tapered male thread tightening torque and through pilot hole, see **P.1224**.

RoHS10

Type	Material	Surface Treatment	Max. Operating Pressure
BTLSN	SS400 Equivalent	Trivalent Chromate	20.6MPa=210kgf/cm <sup>2</sup> or less
BTLSNR	SUS304	-	1MPa=10kgf/cm <sup>2</sup> or less
BTLAN	Aluminum Alloy	-	1MPa=10kgf/cm <sup>2</sup> or less

⚠ The material of BTLAN□-55N is A6063. BTLAN□-55N is for limited space.

Thread: JIS B0203 Rc (PT)

Part Number Type	No.	d Rc(PT)	A	B	L	P	P <sub>1</sub>	P <sub>2</sub>	E	F	Y	d <sub>1</sub>	d <sub>2</sub>	l	Unit Price	
															BTLSN	BTLSNR
BTLSN (Oil Hydraulic) BTLSNR (Water Hydraulic)	1	11	1/8	30	30	40	-	25	-	15						
		22	1/4													
	2	11	1/8	30	30	75	35	60	-	20	15	7	11	6.6	6.5	
		22	1/4													
	3	33N	3/8	40	40						20					
		11	1/8	30	30	110	35	95	-	15						
	*4	22	1/4	30	30	145	35	130	-	20	15	7	11	6.6	6.5	
		33N	3/8	40	40											
	*5	11	1/8	30	30	180	35	165	-	20	15					
		22	1/4													
	*6	33N	3/8	40	40						20					
		11	1/8	30	30	215	35	200	107.5	15						
		22	1/4	40	40					20						

⚠ \* 4, 5 and 6 are available for BTLSN only.

Part Number Type	No.	d Rc(PT) M (Coarse)	A	B	L	P	P <sub>1</sub>	P <sub>2</sub>	E	F	Y	d <sub>1</sub>	d <sub>2</sub>	l	Unit Price	
															BTLSN	BTLSNR
BTLAN (Pneumatic)	1	11	1/8	25	25	40	-	25	-	20	12.5	7	9.5	5.5	5.5	
		22N	1/4	35	35						17.5					
		55N	M5	15	15						30					
	2	11	1/8	25	25	65	25	50	-	20	12.5	7	9.5	5.5	5.5	
		22N	1/4	35	35						17.5					
		55N	M5	25	25						12.5					
	3	11	1/8	25	25	45	15	35	-	15	7.5	3.5	-	4.3	-	
		22N	1/4	35	35						12.5					
		55N	M5	15	15						60					
	4	11	1/8	25	25	90	25	75	-	20	12.5	7	9.5	5.5	5.5	
		22N	1/4	35	35						17.5					
		55N	M5	25	25						12.5					
	5	11	1/8	25	25	115	25	100	-	20	12.5	7	9.5	5.5	5.5	
		22N	1/4	35	35						17.5					
		55N	M5	25	25						12.5					
	6	11	1/8	25	25	75	15	65	-	15	7.5	3.5	-	4.3	-	
		22N	1/4	35	35						12.5					
		55N	M5	15	15						90					
	5	11	1/8	25	25	140	25	125	-	20	12.5	7	9.5	5.5	5.5	
		22N	1/4	35	35						17.5					
		55N	M5	25	25						12.5					
	6	11	1/8	25	25	165	25	150	82.5	20	12.5	7	9.5	5.5	5.5	
		22N	1/4	35	35						17.5					
		55N	M5	25	25						12.5					
		11	1/8	25	25	105	15	95	-	15	7.5	3.5	-	4.3	-	

Ordering Example **Part Number**  
BTLSN2-22  
BTLAN4-22N