

Inclined Blocks

0.1mm Increment

0.1mm increment for each dimension; this block can respond to desired slope shape by specifying angle of gradient.

Part Number		Material
Dimension Configurable	Angle Configurable	
SSRF	SSRAF	SS400
SCRFB	SCRFAF	S50C

SUS303, A5052P are now available online.

Tolerance

A, B, L 50mm or Less	±0.05
A, B, L 50mm or More	±0.1
Circumference Chamfering C0.2	0.5

Dimension Configurable

Angle Configurable

Part Number	0.1mm Increment				
	A	B	L	C	D
SSRF	20.0	10.0	10.0	0.0	2.0
SCRFB	200.0	100.0	200.0	200.0	100.0
		(B≥A/3)		(C≤A)	(D≤B)

Part Number	0.1mm Increment				1° Increment
	A	B	L	C	Q
SSRAF	20.0	10.0	10.0	0.0	0
SCRFAF	200.0	100.0	200.0	200.0	90°
		(B≥A/3)		(C≤A)	1° Increment

Ordering Example Part Number - A - B - L - C - D(Q)
 SSRF - A100 - B80 - L52.3 - C45 - D30.3
 SCRFB - A100 - B80 - L52.3 - C45 - Q55

0.1mm Increment		B: 0.1mm Increment																
		10-30		30.1-40		40.1-50		50.1-60		60.1-70		70.1-80		80.1-90		90.1-100		
A	L	SS400	S50C	SS400	S50C	SS400	S50C	SS400	S50C	SS400	S50C	SS400	S50C	SS400	S50C	SS400	S50C	
20.0-60.0	10-30.0																	
60.1-100.0																		
100.1-130.0																		
130.1-160.0																		
160.1-180.0																		
180.1-200.0	30.1-60.0																	
20.0-60.0																		
60.1-100.0																		
100.1-130.0																		
130.1-160.0																		
160.1-180.0	60.1-100.0																	
180.1-200.0																		
20.0-60.0																		
60.1-100.0																		
100.1-130.0																		
130.1-160.0	100.1-130.0																	
160.1-180.0																		
180.1-200.0																		
20.0-60.0																		
60.1-100.0																		
100.1-130.0	130.1-160.0																	
130.1-160.0																		
160.1-180.0																		
180.1-200.0																		
20.0-60.0																		
60.1-100.0	160.1-180.0																	
100.1-130.0																		
130.1-160.0																		
160.1-180.0																		
180.1-200.0																		
20.0-60.0	180.1-200.0																	
60.1-100.0																		
100.1-130.0																		
130.1-160.0																		
160.1-180.0																		
180.1-200.0																		