



L-Shaped Welded Angles

Dimension Configurable



Type	Material
LSAW	A5052
LSUW	SUS304
T	Tolerance
10, 12	±1.0
15	±1.5



25/(\sqrt{6.3/})

Part Number	A	B	Unit Price										
			LSAW10			LSAW12			LSAW15				
			L50-100	L101-150	L151-200	L50-100	L101-150	L151-200	L50-100	L101-150	L151-200	L201-250	L251-300
LSAW10 LSAW12 LSAW15	101-125	101-125	-	-	-	-	-	-	-	-	-	-	-
	126-150		-	-	-	-	-	-	-	-	-	-	-
	151-175		-	-	-	-	-	-	-	-	-	-	-
	176-200	-	-	-	-	-	-	-	-	-	-	-	-
	101-125	126-150	-	-	-	-	-	-	-	-	-	-	-
	126-150		-	-	-	-	-	-	-	-	-	-	-
	151-175		-	-	-	-	-	-	-	-	-	-	-
	176-200	-	-	-	-	-	-	-	-	-	-	-	-
	101-125	151-175	-	-	-	-	-	-	-	-	-	-	-
	126-150		-	-	-	-	-	-	-	-	-	-	-
	151-175		-	-	-	-	-	-	-	-	-	-	-
	176-200	-	-	-	-	-	-	-	-	-	-	-	-
101-125	176-200	-	-	-	-	-	-	-	-	-	-	-	
126-150		-	-	-	-	-	-	-	-	-	-	-	
151-175		-	-	-	-	-	-	-	-	-	-	-	
176-200	-	-	-	-	-	-	-	-	-	-	-	-	

Part Number	A	B	Unit Price									
			LSUW10		LSUW12		LSUW15					
			L50-100	L101-150	L151-200	L50-100	L101-150	L151-200	L50-100	L101-150	L151-200	
LSUW10 LSUW12 LSUW15	76-100	76-100	-	-	-	-	-	-	-	-	-	
	101-125		-	-	-	-	-	-	-	-	-	
	126-150		-	-	-	-	-	-	-	-	-	-
	151-175	-	-	-	-	-	-	-	-	-	-	
	176-200	-	-	-	-	-	-	-	-	-	-	
	76-100	101-125	-	-	-	-	-	-	-	-	-	-
	101-125		-	-	-	-	-	-	-	-	-	-
	126-150		-	-	-	-	-	-	-	-	-	-
	151-175	-	-	-	-	-	-	-	-	-	-	-
	176-200	-	-	-	-	-	-	-	-	-	-	-
	76-100	126-150	-	-	-	-	-	-	-	-	-	-
	101-125		-	-	-	-	-	-	-	-	-	-
126-150	-		-	-	-	-	-	-	-	-	-	
151-175	-	-	-	-	-	-	-	-	-	-	-	
176-200	-	-	-	-	-	-	-	-	-	-	-	
76-100	151-175	-	-	-	-	-	-	-	-	-	-	-
101-125		-	-	-	-	-	-	-	-	-	-	-
126-150		-	-	-	-	-	-	-	-	-	-	-
151-175	-	-	-	-	-	-	-	-	-	-	-	-
176-200	-	-	-	-	-	-	-	-	-	-	-	-
76-100	176-200	-	-	-	-	-	-	-	-	-	-	-
101-125		-	-	-	-	-	-	-	-	-	-	-
126-150		-	-	-	-	-	-	-	-	-	-	-
151-175	-	-	-	-	-	-	-	-	-	-	-	-
176-200	-	-	-	-	-	-	-	-	-	-	-	-

Long sides of A and B dims.	Perpendicularity k
76-150	0.10 or Less
151-200	0.15 or Less

Alterations Part Number - **A** - **B** - **L** - (CKC, SR, WR-etc.)
 LSAW10 - A120 - B120 - L150 - WR60

Alterations	Corner Cut										
Code	CCA, CCB, CCC, CCD										
Spec.	Any corner can be cut. 1 ≤ Corner Cut ≤ 30 Specify in 1mm increment. <table border="1"> <tr> <th>1mm Increment</th> <th>Unit Price</th> </tr> <tr> <td>1~3</td> <td></td> </tr> <tr> <td>4~10</td> <td></td> </tr> <tr> <td>11~20</td> <td></td> </tr> <tr> <td>21~30</td> <td></td> </tr> </table> Ordering Code (Ex.) When A and D are cut with C5 → CCA5-CCD5	1mm Increment	Unit Price	1~3		4~10		11~20		21~30	
1mm Increment	Unit Price										
1~3											
4~10											
11~20											
21~30											

Alterations	Code	Spec.
	CKC	Both sides of dimension L are machined to be perpendicular to surface A. Ordering Code CKC
	SR	Gusset (6mm) is welded at the center of dimension L. SR ≥ A/2 Ordering Code SR80 (Gusset Height = 80mm from Bottom Surface)
	WR	Two gussets (6mm) are welded 2mm inside from both ends of dimension L. WR ≥ A/2 Ordering Code WR70 (Gusset Height = 70mm from Bottom Surface)

Ordering Example Part Number - **A** - **B** - **L**
 LSAW10 - A120 - B120 - L150